



ASIA'S LEADING
BUILDING PROTECTION
SPECIALIST

NURAPRUFESSTAPE

SPECIALLY FORMULATED PRESSURE SENSITIVE TAPE

DATA SPECIFICATION SHEET

DESCRIPTION

Nuraprufe SS Tape is a specially formulated tape for used together with **Nuraprufe 415** high performance membrane.

The bottom side of the tape has highly aggressive pressure sensitive adhesive which is designed to adhere to **Nuraprufe 415** membrane, penetrations, protrusions etc.

The top side of the tape has a layer of adhesive and a protective coating over it. The protective coating protects the tape from UV light for up to 60 days after application. The tape develops a continuous bond with the concrete that is cast against it.

USES

Nuraprufe SS Tape is used

- To seal fixing points that are not covered by overlapping of 2 different layers of membrane.
- Can be used on details areas including laps and penetrations
- Can be used to patch damaged areas in the Nuraprufe membrane

APPLICATION

Apply **Nuraprufe SS** Tape when ambient temperatures are -4°C (25°F) or above.

Wipe **Nuraprufe 415** membranes clean to remove any dirt, dust or moisture.

Clean surface of fixings, penetrations, protrusions etc to remove loose particle.

Unroll tape and adhere to surface, the protective coating surface should face towards the concrete pour.

Use heavy hand, press in to maximize adhesion.

PRODUCT SPECIFICATION

PACKING SIZE: Rolls and inter-wound with a silicone coated release liner

DIMENSIONS: 120mm width x 50m length per roll

PEEL ADHESION TO CONCRETE: 2872 N/m

RESISTANCE TO HYDROSTATIC HEAD: No Leakage at 7 Bars

Place Product
Sample Here

Hitchins (FE) Marketing Pte Ltd
Telephone: (65) 6861 1177
Facsimile: (65) 6863 4240
Email: hitchins@hitchins.com

Revision B

All data given and statements and recommendations made herein are base upon our research and experience and are believed to be accurate. However, no guarantee of their accuracy is made or applied. This data specification supersedes all other issues.