



ASIA'S LEADING
BUILDING PROTECTION
SPECIALIST

NURAPRUFÉ TAPE

SPECIALLY FORMULATED TWO SIDED PRESSURE SENSITIVE TAPE

DATA SPECIFICATION SHEET

DESCRIPTION

Nuraprufe Tape is a specially formulated two sided pressure sensitive tape. On both sides of the tape has a highly aggressive pressure sensitive adhesive which is designed to stick two different rolls of Nuraprufe 415 membrane together. The tape is a critical component in the Nuraprufe system. It ensures a continuous mechanical bond with the concrete between two separate rolls of Nuraprufe 415 membranes.

It is used in end laps, cut laps and used to lay new Nuraprufe 415 membrane over damaged areas.

Nuraprufe Tape is supplied in rolls with a silicone coated release liner on one side.

APPLICATION

Apply Nuraprufe Tape when ambient temperatures are -4°C (25°F) or above.

Wipe Nuraprufe 415 membranes clean to remove any dirt, dust or moisture.

Unroll the tape over the membrane.

Use heavy hand pressure to maximize adhesion. Remove the release liner during application.

Immediately lay the second roll of Nuraprufe 415 membrane over the tape and use heavy hand pressure to ensure adhesion between different rolls.

PRODUCT SPECIFICATION

DIMENSIONS: 80mm width x 50m length per roll

RESISTANCE TO LEAKAGE AT JOINTS (SS374): Pass

TENSILE SHEAR AT JOINT (SS374)/(ASTM D1204): > 760N

Place Product
Sample Here

Hitchins (FE) Marketing Pte Ltd
Telephone: (65) 6861 1177
Facsimile: (65) 6863 4240
Email: hitchins@hitchins.com

Revision A

All data given and statements and recommendations made herein are based upon our research and experience and are believed to be accurate. However, no guarantee of their accuracy is made or applied. This data specification supersedes all other issues.